

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



INTERNATIONAL BUREAU OF PATENT COOPERATION
358, rue de la Confédération
CH-1202 Genève
Suisse

(43) International Publication Date
30 September 2004 (30.09.2004)


PCT

(10) International Publication Number
WO 2004/083900 A2

- (51) International Patent Classification: **G02B**
- (21) International Application Number: **PCT/IB2004/000792**
- (22) International Filing Date: **9 March 2004 (09.03.2004)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
03100687.7 18 March 2003 (18.03.2003) EP
- (71) Applicant (for DE only): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).**
- (71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N. V. [NL/NL]; Groenewoudseweg 1, 5621 BA Eindhoven (NL).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): **LESCH, Norbert [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE). TRAA, Willebrordus Gerardus [NL/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).**
- (74) Agent: **VOLMER, Georg; Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).**
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM.**

[Continued on next page]

(54) Title: **GAS DISCHARGE LAMP**



(57) Abstract: A gas discharge lamp (1) is described with a discharge vessel (2) and electrodes (4, 5) projecting into the discharge vessel (2). The gas discharge lamp (1) is provided with a translucent, electrically conductive screening (9, 23) which screens the discharge vessel (2) and which comprises connection means (7, 10, 24, 27, 28). The screening (9, 23) of the gas discharge lamp (1) is connected to a screening (14, 17, 19) of an electrical system used for operating the gas discharge lamp (1) at least as regards high frequencies so as to form a coaxial screening system that encloses the discharge vessel (2) with its electrodes (4, 5).